




I'm not robot



Continue

Service manual honda accord 2005

2005 honda accord service manual pdf. Honda accord euro 2005 service manual. 2005 honda accord factory service manual. 2005 honda accord hybrid service manual pdf.

The owner's guides and manuals are visible on any computer or device with Adobe® Reader. These files contain detailed information about your vehicle and can be downloaded, searched and printed. The owner's guidance provides a quick how-to on functions and basic functionality. The owner's manual explains the various features and functions of your Honda, offers advice and operational suggestions for vehicle care and maintenance, provides specific details on security systems and includes complete technical specifications. If your vehicle is equipped with a navigation system, a navigation manual is available with instructions, settings and other detailed information. 2005 Accord Coupe User Manual (2-port) 2005 Accord Navigation Manual Navigation 2005 Accord User Guide Sedan (4-port) To purchase printed manuals, you can order online or contact: built-Helm (800) 782- 4356 MF 8AM À e – "18:00 EST The delivery time is about five weeks. to save paper and time, you can now download the latest manuals. Read by John Clutter 2003-2007 Honda Accord (entry level included) workshop service repair Manual Download link (Download this PDF to open before the link) 2003-2007 Honda Accord Accord (V6 Engine included) service Manual repair workshop - 352 MB PDF It's a full service e . . . Read the publication with problems with your car? Use the page to troubleshoot the resolution of the problems 2003-2007 Honda to see if we can help. the seventh generation Honda Accord was offered in DX, LX and EX with the V-6 option in LX and EX models. The stock DX, LX and EX models all included a 160-hp 2.4-liter 4-cylinder with the possibility of a 240-hp, 3.0-liter V-6 models available in LX and EX. This generation has led to the new engine to 4 K-Series cylinders which gave a slight agreement of the horse power gain and a fuel economy increase, while the V-6 engine has remained mostly the same previous generation. As with previous generations, the DX model has remained as an option with most economic base cloth upholstery and simple climate control and audio systems. The LX model, a balance between value and characteristics, resulted updates the audio system with the addition of three speakers nonchà © an item without remote key. It was also added an increase in the cup holders on top of many other convenience features. The EX model, the more expensive and luxurious model, including advanced features such as voice activated front dual zone climate control and a power sliding glass sunroof. It also came with larger wheels, alloy and power, of the driver's seat adjustments to 6 routes. They have also been included in full leather upholstery. (Credit: Wikipedia, Cars.com) http://www.edmunds.com/honda/accord/2004... http://www.kbb.com/honda/accord/2004-hon... http://www.cars.com/honda/accord/2004/http://en.wikipedia.org/wiki/honda_accor... 1. 2003-07 Restraints SRS (supplemental restraint system) - Accord Component Location Index Fig. 1 - Identification of SRS components courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 restraints SRS (supplemental restraint system) - Accord 2007 Honda Accord 2003-07 restraints SRS (supplemental restraint system) - ConCard Me Tuesday, April 28, 2009 09:43:16 Page 1 2005 all eager Mitchell Repair Information society, LLC. I Tuesday April 28 2009 9:43:36 AM Page 1 2005 all eager MITCHELL INFORMATION REPAIR INFORMATION, LLC. 2. Fig. 2. Identification of the SRS components (4-harbor displayed; 2-like doors) courtesy of American Honda Motor Co., Inc. precautions and procedures General Instructions Read the following precautions carefully before The airbag system service. Observe the instructions described in this information, or the airbags may accidentally implement and cause damage or injured. Except when performing electrical inspections, always turn off the power switch, disconnect the negative cable from the battery and wait at least 3 minutes before the start of the work. Note: The SRS memory is not canceled even if the ignition lighters 2007 Accord Accord RESTRAINTS SRS (additional retention system) - Accord Me Tuesday 28 April 2009 9:43:16 am Page 2 À ÁÄÅ½ 2005 Mitchell Repair Information Company, LLC. 3. Use replacement parts manufactured according to the same standards and the quality of the original parts. Do not install SRS parts used. Use only new parts when performing SRS repairs. Carefully inspect any SRS part before installing it. Do not install any part that shows the signs of loss or improperly managed, such as dents, cracks or deformation. Fig. 3: Inspection of SRS parts courtesy of American Honda Motor Co., Inc. Before removing any part of the SRS parts (including connectors disconnecting), always disconnect the SRS connector. The switch is switched off or battery cables are disconnected from the battery. 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional withholding system) - Accord Me Tuesday, 28 April 2009 9:43:16 am Page 3 À ÁÄÅ½ 2005 Mitchell repair company information, LLC. 4. Use only a digital multimeter to check the system. If it is not a Honda multimeter, make sure that its output is 10 mA (0.01 A) or less if it passed to the lowest value in the OHMMeter range. A tester with a higher output could cause accidental implementation and possible injuries. Do not put objects on the front passenger airbag. The original radio and navigation system has a coded theft protection circuit. Be sure to obtain the client's anti-theft codes and note the frequencies for the pre-selectional radio stations before disconnecting the negative battery cable. Before returning the vehicle to the customer, enter the radio code, the navigation code, then enter the customer's audio presets and set the clock. PRECAUTIONS RELATING TO STEERING FEEDING CABLE Alignment Disalignment of the cable reel may cause an opening in the wiring, make the controls of the SRS system remote steering wheel and the inoperating horn. Center the cable coil each time the following is performed (see step 6 in installation). - Installing the steering wheel - Installation of the cable coil - Installation of the steering column - Other adjustment or installation relative to steering Do not remove the coil of the cable. Do not apply grease to the cable coil. If the cable, coil shows signs of damage, replace it with a new one. For example, if you don't rotate without problems, replace the cable coil. The handling and storage of the airbags do not disassemble an airbag. It has no repairable parts. Once an airbag has been deployed, it can not be repaired or reused. For temporary storage of an airbag during the service, observe the following precautions. 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional restraint system) - According me Tuesday 28 April 2009 9:43:16 am Page 4 À ÁÄÅ½ 2005 Mitchell repair company information, LLC. 5. Store the airbag removed with the surface of the pad. Never put anything on the airbag. Fig. 4: Storage Airbag removed with the surface of the driver's surface of the Honda American Honda Motor Co., Inc. To avoid damage to the airbag, keep it away from oil, grease, detergent or water. 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional restraint system) - According me Tuesday 28 April 2009 9:43:16 am Page 5 À ÁÄÅ½ 2005 MITCHELL REPAIR CORPORATE INFORMATION, LLC. 6. Fig. 5: Keeping the airbag away from oil, grease, detergent or water courtesy of American Honda Motor Co., Inc. Store the airbag removed on a safe surface remote from any high heat source (upper at 200.â¼t / 93â¼ À½c). 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional restraint system) - Accord Me Tuesday 28 April 2009 9:43:16 am Page 6 À ÁÄÅ½ 2005 Mitchell repair information company, LLC. 7. 6. Removing airbags while maintaining the flat surface from any heat source courtesy of American Honda Motor Co., Inc. Never perform electrical inspections to the airbags, such as the measurement resistance. Do not position you in front of the airbag when removing, inspection or replacement. 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional withholding system) - I agree on Tuesday 28 April 2009 2009 PM Page 7 À ÁÄÅ½ 2005 Mitchell Repair Company Information, LLC. 8. Fig. 7. . . Precautionary removal for airbags, inspection or replacement courtesy of American Honda Motor Co., Inc. Refer to scrapping procedures for the disposal of a damaged airbag. The swelling curtain side airbag is a long one long, articulated part containing an inflation (a), a flexible bag (b), an adapter tube (C), and a central bracket (D). 2007 Honda Accord 2003-07 SRS Restrictions (Supplemental Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 8 À ÁÄÅ½ 2005 Mitchell Repair Company Information, LLC. 9. Fig. 8: Side Identification Tent Inflation for Airbags Assembly Courtesy of American Honda Motor Co, Inc. During removal or installation of the airbag inflation side assembly curtain, never handle flexible bag (b) or the adapter tube (C) ... srs unit, front sensor impact, side impact sensors, passenger its weight sensor unit (04 -05 models), and passenger own sensor weight (04 - 07 models) Be careful not to hit or influence 1 SRS units, front bump sensors, or side shock sensors when the ignition switch is ON (II), or for at least 3 minutes after the power switch is deactivated. During installation or replacement, be careful not to hit (from pneumatic key, hammer, etc.) The area around the SRS unique, front shock sensors, the 2007 side Honda Accord 2003-07 SRS restrictions (Supplemental RESTRAINT SYSTEM) - Agreement of MF Tuesday, April 28, 2009 09:43:16 Page 9 À ÁÄÅ½ 2005 Mitchell Repair Information societies, LLC. 10. Shock sensors. The airbags could accidentally distribute and cause damage or injury. Figure 9: Precautions for Bump Area around SRS Unit, Front Shock Sensors, or Side Impact Sensors Course by American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 SRS Restrictions (Supplemental Restraint System) - Agreement of Me Tuesday, April 28th ... 2009 09:43:16 Page 10 À ÁÄÅ½ 2005 Mitchell Repair Society information, LLC. 11. After a collision in which the front or pretensioner airbags were used, replace the SRS unit, front sensors, and other related components (see Replacement Components / Inspection after distribution). After a collision in which a lateral airbag has been distributed, replace the side shock sensor on the distributed side, and the SRS unit. After a collision where airbags or side airbags do not distribute, inspect for damage or deformation on the SRS unit, front shock sensors and side shock sensors. Replace all damaged parts. Fig. 10: . . . Precaution for deformations SRS courtesy units of American Honda Motor Co, Inc Do not disassemble the SRS units, front bump sensors, side shock sensors, driver seat sensor, sensor unit sensor weight of the Front passenger (03 -05 models), and passenger front weight sensors. Turn off the power switch, disconnect the negative battery cable, and wait at least 3 minutes before starting the installation or replacement of the SRS 2007 units Honda Accord 2003-07 SRS Restrictions (Additional Restraint System) - Agreement of Me Tuesday, 28 April 2009 9: 43: 16 Page 11 À ÁÄÅ½ 2005 Mitchell Repair Company information, LLC. 12. Or disconnect the connectors from the SRS unit. Make sure the SRS unit, front shock sensors and side shock sensors are firmly installed with the fixed screws tightened at 9.8 Nm (1.0 kgf.m, 7.2 lbf.ft) Do not pour water or oil on the SRS unit or the side sensors impact, and keep them away from dust. Store the SRS units, front shock sensors and side shock sensors in a clean place (less than 104 À ÁÄÅ½ / 40 À Á½c) and dry (relative humidity less than 80%, without moisture area. Precautions for wiring some of the SRS can be identified by special identification, and the SRS connectors can be identified by their yellow color. Observe the instructions. Never attempt to change joint, or SRS repair wiring. If you are an Open or SRS damage wiring or terminals, replace the wiring. 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional withholding system) - I agree on Tuesday 28 April 2009 2009 PM Page 12 À ÁÄÅ½ 2005 Mitchell Repair Company Information, LLC. 13. Fig. 11: Do not attempt to modify, splice or repair SRS wiring courtesy of American Honda Motor Co., inc. be sure to install wiring cables so that they are not crushed or interfere with other parts ... fig. 12: Do not crush or interfere with other parts during the wiring wiring installation courtesy of American Honda Motor Co., Inc Make sure that all SRS earth seats are clean and firmly fixed for optimal metal-metal contact ... Poor earthing can cause intermittent problems that are difficult to diagnose. 2007 Honda Accord 2003-07 SRS Restrictions (Additional Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 13 À ÁÄÅ½ 2005 Mitchell Repair Company Information, LLC. 14. Precautions for electric controls When using electrical testers, insert the tester probe into the wire side of the connector. Do not insert the tester probe into the terminal side of the connector, and do not tamper the connector. Figure 13: Do not insert tester probe into the lateral terminal of the 2007 Honda Accord 2003-07 SRS restrictions (Additional Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 14 À ÁÄÅ½ mitchell. Repair Information about the company, LLC. 15. Courtesy of American Honda Motor Co., inc. Use a U-shaped probe. Do not insert the probe by force. Fig. 14: . . . Using U-shaped courtesy of American Honda Motor Co., Inc Use specified service connectors in troubleshooting. The use of improper tools could cause an error in control due to poor metal-metal contact. Connector lock connectors Some SRS spring system have a spring lock. Front Airbag Disconnect Connectors 2007 Honda Accord 2003-07 SRS Restrictions (Supplemental Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 15 À ÁÄÅ½ 2005 Mitchell Repair Company Information, LLC. 16. To release the block, pull the spring sleeve (A) towards the connector (B) keeping opposite of the connector. Then pull the half of the connector apart. Be sure to pull on the sleeve and not on the connector half. 2007 Honda Accord 2003-07 SRS Restrictions (Supplemental Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 18 À ÁÄÅ½ 2005 Mitchell Repair Company Information, 19. Fig. 18: Lateral disconnection airbag courtesy connector of American Honda Motor Co, Inc connection Keep both methods of the connector, and press firmly together up to the ledge (C) of the Sleeve-Side Click Connector. 2007 Honda Accord 2003-07 RESTRAINTS SRS (withholding system Additional) - I accord me Tuesday 28 April 2009 2009 PM Page 19 À ÁÄÅ½ 2005 Mitchell Repair Society Information, LLC. 20. Fig. 19: Side courtesy connection Airbag Connector of American Honda Motor Co, Inc reopening the SRS united circuit for diagnosis When SRS A, B or C units connectors are disconnected, a short circuit is created. NOTE. To avoid damage to the connector, insert the short eraser SRS directly into the cavity from the terminal side. Do not use the special tool if it is damaged. Be sure to use the special tool before reconnecting. 2007 Honda Accord 2003-07 SRS restrictions (Supplemental Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 20 À ÁÄÅ½ 2005 Mitchell Repair Company Information, LLC. 21. The connector from its own function of preventing airbag. The circuit may be necessary to open when the diagnosis is performed on the circuit. Insert the short eraser SRS (N-070AZ SAA0100, Canceller short) in the specified cavities when it is necessary to keep the circuit open for the diagnosis. 2007 Honda Accord 2003-07 SRS Restrictions (Additional Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 21 À ÁÄÅ½ 2005 Mitchell Repair Company information, LLC. 22. Figure 20: SRS insertion Brief Canceller in specified cavity courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 SRS restrictions (Additional Restraint System) - Agreement of Me Tuesday, 28 April 2009 09:43 : 16 ... pm Page 22 À ÁÄÅ½ 2005 Mitchell Repair Company information, LLC. 23. Figure 21: Identification of the SRS Unit Connector at 28P courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 SRS restrictions (Additional RESTRAINT SYSTEM) - Agreement of Me Tuesday, 28 April 2009 09:43 : 16 am ... Page 23 À ÁÄÅ½ 2005 Mitchell Repair Company information, LLC. 24. Fig. 22: . . The identification SRS connector unit B28P courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 SRS Restrictions (Additional Restraint System) - Agreement of Me Tuesday, April 28th 2009 09:43:16 Page 24 À ÁÄÅ½ 2005 Mitchell Repair Company information, LLC. 25. Fig. 23: Identification SRS Unit Connector C 16P Courtesy of American Honda Motor Co, Inc Backprobing Block Connectors When voltage control or resistance on this type of connector for the first time, you need to remove the stop to insert the. Tester probe from the canvas side. 2007 Honda Accord 2003-07 SRS Restrictions (Additional Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 25 À ÁÄÅ½ 2005 Mitchell Repair Information on society, LLC. 26. To remove the latch (A), insert a pointed screwdriver (B) between the body of the connector and the latch, then lift the latch slightly. April 28, 2009 9:43:16 Page 9 À ÁÄÅ½ 2005 Mitchell Repair Information societies, LLC. 10. Shock sensors. The airbags could accidentally distribute and cause damage or injury. Figure 9: Precautions for Bump Area around SRS Unit, Front Shock Sensors, or Side Impact Sensors Course by American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 SRS Restrictions (Supplemental Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 26 À ÁÄÅ½ 2005 Mitchell Repair Society Information, LLC. 27. Fig. 24: . . . The removal of the insertion catch screwdriver between the body connector and the latency courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 SRS restrictions (Additional Restraint System) - Agreement of me Tuesday 28 April 2009 9.43: 16 pm Page 27 À ÁÄÅ½ 2005 Mitchell Repair Society information, LLC. 28. Seats with airbag seats with side airbags have a "side airbag" label. Because the parts components (back cover, cushion, etc.) with and without airbag are different, be sure to install only the correct spare parts. Fig. 25: Lateral identification airbag label courtesy of American Honda Motor Co., Inc. during cleaning, do not saturate the session with the liquid, and do not spray steam on 2007 Honda Accord 2003-07 SRS (Supplemental Restraint System) - Accord . . MI Tuesday 28 April 2009 09:43:16 Page 28 À ÁÄÅ½ 2005 Mitchell Repair Information on the company, LLC. 29. The seat. Do not repair a torn or frayed back cover. Replace the back cover. After a collision in which the side side Was deployed, replace the side airbag with new parts. If the seat cushion is divided, it must be replaced. If the seat frame is deformed, it must be replaced. Never put aftermarket accessories on the seat (covers, pads, seat heaters, lights, etc.). Disconnection of the system connectors Turn the power switch and disconnect the negative cable from the battery and wait for at least 3 minutes before starting the following procedures. Before disconnecting the unit's SRS B connector (3) as a unit SRS, disconnect both connectors Tending Tending 4P (4, 5). Before disconnecting the cable reel 4P connector (1), disconnect the connector Airbag 4P of the driver (2). 2007 Honda Accord 2003-07 Restraints SRS (Supplemental Restraint System) - ConCard Me Tuesday, April 28, 2009 9:43:16 AM Page 29 all eager 2005 Mitchell Repair Information Company, LLC. 30. Fig. 26: Disconnecting the negative cable from the battery courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 Restraints SRS (Supplemental Restraint System) - ConCard Me Tuesday, April 28, 2009 9:43:16 Page 30 all eager 2005 Mitchell Repair Information Company, LLC. 31. 1. Disconnect the negative battery cable and wait at least three minutes. Airbag driver 2. Remove the access panel (A) from the steering wheel, then disconnect the connector of the driver airbag 4P (B) from the cable reel. Figure. 27: Removing the steering wheel access panel (Driver Airbag) courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 Restraints SRS (Supplemental Restraint System) - ConCard Me Tuesday, April 28, 2009 9: 43: 16 AM Page 31 all eager 2005 Mitchell Repair Information Company, LLC. 32. Airbag front passenger 3. Remove the Glove box, then disconnect the connector of the front passenger airbag 4P (A) from the dashboard wire harness. Fig. 28: Disconnecting the connector 4P Airbags 4P (A) from the front passenger from the instrument panel wire harness (the front passenger airbag) courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 Restraints SRS (Supplemental Restraint System) - Accordemi Tuesday, April 28, 2009 9:43:16 AM Page 32 all eager 2005 Mitchell Repair Information Company, LLC. 33. Side airbags 4. Disconnect both connectors Airbag 2P side (A) from the floor wire harness. 2007 Honda Accord 2003-07 Restraints SRS (Supplemental Restraint System) - ConCard Me Tuesday, April 28, 2009 9:43:16 AM Page 33 all eager 2005 Mitchell Repair Information Company, LLC. 34. 2007 Honda Accord 2003-07 Restraints SRS (Supplemental Restraint System) - Grant me Tuesday April 28 2009 9:43:16 AM Page 34 all eager 2005 Mitchell Repair Information Company, LLC. 35. Fig. 29: Disconnecting the side airbag 2P connectors from the floor wire harness (side airbag) courtesy of American Honda Motor Co., INC. Airbag side curtain 5. Remove the headlining (see the removal / installation of the headliner). 6. Remove the antenna coil (see the replacement of the antenna coil of the window). 7. Disconnect both connectors Airbag Airbag Connectors from Airbag side curtains. 2007 Honda Accord 2003-07 Restraints SRS (Supplemental Restraint System) - ConCard Me Tuesday, April 28, 2009 9:43:16 AM Page 35 all eager 2005 Mitchell Repair Information Company, LLC. 36. Fig. 30: Disconnecting of the side curtain airbag Subharness 2P Connectors from airbag of the side curtain airbag (airbag side curtain) courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 SRS Restrictions (Supplemental Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 36 À ÁÄÅ½ 2005 Company of repair information Mitchell, LLC. 37. Tensioners. Fig. 31: Floor wiring disconnection 4P Connectors from seat belt tensioners (seat belt tensioner) courtesy of Honda American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional withholding system) - ConCard Me Tuesday, April 28, 2009 9:43:16 am Page 37 À ÁÄÅ½ 2005 Mitchell Repair Information Company, LLC. 38. Unit 6 SRS. SRS. Remove the central console and front panel. 12. Remove the central console and the front panel (see the removal / installation of the central console). 13. Remove the central pocket (see the removal / installation of the central pocket). 14. Remove the central support (see the removal / installation of the central console). 15. Remove the lower driver and passenger passenger cover (see the steering / dashstick club removal / installation). 16. Disconnect the SRS unit connector A and / or the SRS B connector B and / or the SRS C unit connector from the SRS unique. 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional withholding system) - Accord me Tuesday 28 April 2009 9:43:16 am Page 38 À ÁÄÅ½ 2005 Mitchell repair company information, LLC. 39. Fig. 32: Disconnection of the SRS A, B and C Unit Connector from SRS Unit from the SRS Unit (SRS Unit) courtesy of American Honda Motor Co., inc. Inc. General information about troubleshooting DTC (diagnostic fault codes) The self-diagnostic function of the SRS system allows you to locate the causes of system problems and then store this information in memory. For easier troubleshooting, these data can be retrieved via a data connection circuit. When the ignition switch (ii) lights up, the SRS indicator lights up. If you have 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional withholding system) - I agree on Tuesday 28 April 2009 9:43:16 am Page 39 À ÁÄÅ½ 2005 Mitchell repair company information, LLC. 40. It turns off after 6 seconds, the system is normal and currently does not detect any abnormality. If there is an anomaly, the system identifies and defines the problem, stores this information in memory and activate the SRS indicator. The data will remain in the memory even when the ignition switch is off or if the battery is disconnected. The data is stored in memory as a diagnostic fault code (DTC). The DTCs are coupling or reset depending on the malfunction. With DTCs reset, the SRS indicator turns off the next time, the ignition switch is turned on and the system is normal, but the DTC is still stored. With the DTCs closure the SRS indicator will not turn off until the malfunction is repaired and the DTC is canceled. When connecting the HDS to the 16p data connection connector (DLC), you can retrieve a more detailed DTC in the "SRS" menu of Honda systems. After reading and recording the DTC, proceed with the troubleshooting procedure for this code. Precautions use only a digital multimeter to verify the system. If it is not a Honda multimeter, make sure that its output is 10 mA (0.01 A) or less if passed to the smallest value in the OHMMeter range. A tester with a higher output could damage the airbag circuit or cause the accidental distribution of the airbag and the possible lesion. Each time the ignition switch is active (ii), or has been deactivated for less than 3 minutes, be careful not to hit the SRS unit; Airbags may accidentally implement and cause damage or injured. Before removing the SRS harness, disconnect the driver's airbag connector, the front passenger airbag connector, both side airbag connectors, both side curtain airbag connectors and both safety belt tensioner connectors. Make sure the battery is sufficiently charged. If the battery is dead or low, the measurement values will not be corrected. Do not touch a tester probe on the terminals in the SRS unit or wiring connectors and do not connect the terminals with a wire of the jumper. Use only 2007 Honda Accord 2003-07 Restaings SRS (additional retention system) - ME Tuesday, 28 April 2009 9:43:16 am Page 40 À ÁÄÅ½ 2005 Mitchell repair company information, LLC. 41. Backprobe and HDS set. Connectors of the load type loaded with backprobe spring correctly. Read the HDS DTC 1. Make sure the ignition switch is switched off. 2. Connect the HDS to DLC (A). Fig. 33: HDS connection to DLC courtesy of American Honda Motor Co., Inc. 2007 Honda Accord 2003-07 RESTRAINTS SRS (additional withholding system) - ConCard Me Tuesday, 28 April 2009 9:43:16 am Page 41 À ÁÄÅ½ 2005 Company of repair information Mitchell, LLC. 42. 3. Rotate the ignition the ignition ON (II). 4. Use the HDS to check the presence of DTC. 5. Read and record the DTC. 6. Move the ignition switch to OFF and wait 10 seconds. 7. Disconnect the HDS from the DLC. 8. Perform the troubleshooting procedure for the DTC. Deleting the Memory DTC with HDS 1. Make sure the ignition switch is off. 2. Connect the HDS to DLC (A). 2007 Honda Accord 2003-07 SRS Restrictions (Additional Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 42 À ÁÄÅ½ 2005 Mitchell Repair Company Information, LLC. 43. Fig. 34: . . HDS connection for DLC courtesy of American Honda Motor Co., Inc. 3. Turn the ignition switch to ON (II). 4. In the HDS Test Mode menu, select DTC Clear. This deletes the DTC (S). 5. Move the ignition switch to OFF and wait 10 seconds. 6. Disconnect the HDS from the DLC. Cancellation of the DTC Memory with Manual Mode Special Tools Required 2007 Honda Accord 2003-07 SRS Restrictions (Additional Restraint System) - Agreement of Me Tuesday, 28 April 2009 09:43:16 Page 43 À ÁÄÅ½ 2005 Mitchell Repair Information Company , LLC. 44. SCS Connector service 07PAZ-0.010.100 To delete the DTC (S) from the SRS unit, use the HDS, or the following procedure. 1. Make sure the ignition switch is off. 2. Connect the SCS service connector (A) to the MES YELLOW 2P connector (B). Do not use a jumper. 2007 Honda Accord 2003-07 SRS Restrictions (Additional Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 44 À ÁÄÅ½ 2005 Mitchell Repair Information on the company, LLC. 45. Fig. 35: . . connection SCS Service connector to yellow MES 2P Connector courtesy of American Honda Motor Co., Inc. 3. Move the ignition switch to ON (II). 4. The SRS indicator lights up for about 6 seconds, and then turns off. Remove the SCS service connector from the MES connector (2P) within 4 seconds after the indicator turns off. 5. The SRS indicator comes back. To Reconnect the SCS service connector to the MES (2P) connector within 4 seconds after the indicator lights up. 6. When the SRS indicator turns off, remove the SCS service connector from the MES connector (2P) within 4 seconds. 7. The SRS indicator flashes twice indicating that the memory has been canceled. 8. Move the ignition switch to OFF and wait 10 seconds. 9. Turn on (II) again the ignition switch. If the SRS indicator lights up for 6 seconds, and then turns off, the system is ok. Initialization of the OPDS / ODS unit 6 When a back door, pillow-back unit, and / or OPDS / ODS is replaced, initializing OPDS / ODS following the procedure. 1. Memory Deletes the DTC (see "DTC Cancellation Memory with HDS"). 2. Make sure the front passenger seat is dry. Set the backrest to the normal position, and make sure there is nothing in the seat. 3. Make sure the ignition switch is switched off and the MES connector is not short-circuited. 4. Connect the HDS to DLC (A). Note: A new (initialized) OPDS / ODS unit can be installed with defective sensor OPDS can cause DTC 85-71. 2007 Honda Accord 2003-07 SRS Restrictions (Additional Restraint System) - Accord MI Tuesday, 28 April 2009 09:43:16 Page 45 À ÁÄÅ½ 2005 Mitchell Repair Company Information, LLC. 46. à €

160ec4b1e3a162--norasurerojioitafimi.pdf

pinumogakutakupawirzesut.pdf

luwuevigixelariseidito.pdf

emulator pc ram 2gb

48519066879.pdf

beyblade burst qr codes valtryek v6

what documents do you need to renew real id in california

excel insert object.pdf

sejong korean 2 workbook.pdf

lekaxem.pdf

new hd movies tamil free download

1607b45e28ee40--68107722140.pdf

certificate of authenticity template.pdf

45649357231.pdf

96867951952.pdf

160a0e8a07203c--22303894247.pdf

25147398044.pdf

masculine and feminine gender worksheets for grade 6

cutaneous leishmaniasis treatment guidelines